COR 3000

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient
Uw from 1.3 (W/mK)²
Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: 1.22"
Maximum accoustic insulation: Rw = 46 dB.

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):	Class 4
Water tightness (UNE-EN 12208:2000):	Class 9A
Wind resistance (UNE-EN 12210:2000):	Class C5

Reference test window 46.46" × 46.46" 2 sashes.

SECTIONS	Frame 1.77" Sash 2.09"
PROFILE THICKNESS	Window 0.059" Balcony 0.067"
MAXIMUM DIMENSIONS	Width (L) = 59.06" Height (H) = 94.49"
MAXIMUM WEIGHT/SASH	120 Kg.

Please consult maximum dimensions according to types.

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured
HERRAJE	Optionally concealed hinges Optionally security hardware

EXTRUSION ALLOY
6063 T-5

POLYAMIDE STRIP LENGTH
Polyamide 6.6 reinforced with 25% fiberglass : 0.57"

GASKETS
EPDM triple gasket

FOAMS
Perimeter polyolefin foam in glazing rebate zone

OPENING POSIBILITIES	
INWARDS	Side hung, turn & tilt, bi-fold, tilt and paralel tilt
OUTWARDS	Side hung, top hung and horizontal and pivoting on horizontal or vertical axis

